

消防用ねじ寸法表

消防用ねじ式結合金具

JIS B 9912

呼称寸法	めねじ内径寸法 (D ₁)	おねじ外径寸法 (D ₂)	山/吋	ピッチ (P)
20	22.378~22.188	24.750~24.560	10	2.540
25	30.834~30.474	33.700~33.490	8	3.175
30	36.834~36.474	39.700~39.490	8	3.175
40	44.834~44.474	47.700~47.490	8	3.175
50	56.834~56.474	59.700~59.490	8	3.175
65	77.294~76.834	82.040~81.770	5	5.080
75	88.388~87.888	94.450~94.140	4	6.350
90	103.388~102.888	109.450~109.140	4	6.350
100	115.888~115.388	121.950~121.640	4	6.350
115	133.388~132.888	139.450~139.140	4	6.350
125	143.388~142.888	149.450~149.140	4	6.350
140	158.388~157.888	164.450~164.140	4	6.350
150	168.388~167.888	174.450~174.140	4	6.350

消防用ノズルチップ結合金具

JIS B 9913

呼称寸法	めねじ内径寸法 (D ₁)	おねじ外径寸法 (D ₂)	山/吋	ピッチ (P)
40	33.820~33.660	35.790~35.630	12	2.117
50	42.820~42.660	44.790~44.630	12	2.117
65	52.378~52.188	54.750~54.560	10	2.540
75	65.378~65.188	67.750~67.560	10	2.540

米国消防ねじ式結合金具

American National Fire Hose Connection Screw Threads (NH)

呼称寸法	めねじ内径寸法 (D ₁)	おねじ外径寸法 (D ₂)	山/吋	ピッチ (P)
3/4", 1"	31.668~31.105	34.925~34.361	8	3.175
1 1/2"	47.749~47.185	50.546~49.984	9	2.822
2 1/2"	74.737~73.924	77.942~77.129	7 1/2	3.386
3"	87.840~86.926	92.047~91.132	6	4.233
3 1/2"	103.715~102.801	107.795~106.880	6	4.233
4"	120.932~119.662	127.277~126.007	4	6.350
4 1/2"	139.981~138.712	146.326~145.058	4	6.350
5"	152.659~151.389	159.004~157.734	4	6.350
6"	172.090~170.820	178.435~177.165	4	6.350

米国ホース用ねじ式結合金具

American Standard Hose Coupling Screw Threads (ANSI B33.1)

1 1/2"	45.519~45.165	47.721~47.289	1 1/2	2.208
2"	57.576~57.144	59.766~59.329	1 1/2	2.208

